

Airbag enable-disable switch potentiometer

Main features


- Fully customisable electromechanical switch.
- Mechanical life: 15.000 cycles.
- Operating voltage: 13.5±0.2 VDC.
- Operating temperature: -40°C to +85°C
- Torque: ≤ 2Ncm.
- Switch angle: customisable.
- For other specifications please refer to S-2S6T-14B268-AA.

Description

Airbags have been designed to help protect adults in a moderate to severe frontal collision. To do this, the passenger's front airbag is quite large, and it can inflate with enough force to cause very serious injuries.



There are conditions where the automatic shut off feature will not completely insure safety (seat too far forward, small child in a car seat), there could be a need to manually disarm the passenger side airbag.

Even though the vehicle may include an advanced front airbag system that automatically turns the passenger's front airbag off, all manufacturers offer a manual cutoff system for an additional measure of safety.



These manual systems are typically activated or deactivated by turning them using the vehicle's ignition key.

Piher has developed a rotary switch that seamlessly adapts to these systems and reliably actuates the transition between the "on" and "off" states.



Information contained in and/or attached to this document may be subject to export control regulations of the European Community, USA, or other countries. Each recipient of this document is responsible to ensure that usage and/or transfer of any information contained in this document complies with all relevant export control regulations. If you are in any doubt about the export control restrictions that apply to this information, please contact the sender immediately. For any Piher Sensors & Controls Exports, Note: All products / technologies are EAR99 Classified commodities. Exports from the United States are in accordance with the Export Administration Regulations. Diversion contrary to US law is prohibited.