



PC-16

16-mm carbon panel mount potentiometer

The PC-16 is a single-turn panel control potentiometer using a carbon resistive element with plastic housing and incorporated shaft. A wide variety of configurable options, such as single or tandem models, different shaft types and tapers, make the PC-16 suitable for numerous applications in the home appliance and industrial markets.



KEY FEATURES

- ▶ IP54 protection according to IEC 60529
- ▶ Single and tandem models
- ▶ Housing and bushing made of self extinguishable material UL 94-V0
- ▶ Selection of plastic and metal shafts
- ▶ Linear, log (audio) and antilog (reverse) tapers
- ▶ Solder lugs or PC pins

On request

- ▶ Stereo matching
- ▶ Rotary switch
- ▶ Nut & washer
- ▶ Bushless & shaftless models
- ▶ Assemblies with wires and connectors
- ▶ Metallic support (mounting brackets)

ELECTRICAL SPECIFICATIONS

Taper	Lin, Log, Alog
Range of values* (Decad. 1.0 - 2.0 - 2.2 - 2.5 - 4.7 - 5.0)	
Lin	$100\Omega \leq R_n \leq 5M\Omega$
Log, Alog	$1K\Omega \leq R_n \leq 5M\Omega$
Tolerance*	
$100\Omega \leq R_n \leq 1M\Omega$	$\pm 20\%$
$1M\Omega < R_n \leq 5M\Omega$	$\pm 30\%$
Max. Voltage	
Lin	250 VDC
Log, Alog	125 VDC
Nominal power 50°C (122°F)	
Lin	0.2 W
Log, Alog	0.1 W
Residual resistance	$\leq 5\% R_n$ (5Ω min.)
Equivalent noise resistance	$\leq 3\% R_n$ (3Ω min.)
Operating temperature**	-25°C to +70°C (-13°F to + 158°F)

* Others: check availability ** Up to 85°C depending on application

APPLICATIONS

- ▶ Appliance program selection
- ▶ Thermostat adjustment
- ▶ HVACR control
- ▶ Consumer electronics
- ▶ Industrial controls
- ▶ Healthcare / laboratory devices
- ▶ Home and building automation

PC-16

16-mm carbon panel mount potentiometer

MECHANICAL SPECIFICATIONS

Mechanical rotation angle	300° ±5°
Electrical rotation angle	
Only Potentiometer	280° ±20°
Potentiometer with rotary switch	240° ±20°
Rotational torque ¹	0.5 to 1.5 Ncm (0.7 to 2.1 in-oz)
Stop torque	> 40 Ncm (>56 in-oz)
Max. torque nut (binding out)	< 80 Ncm (<112 in-oz)
Push and pull in the shaft	> 25 N
Life	
Potentiometer	25.000 cycles ²
Switch	10.000 cycles

¹ For single models. Tandem versions have a higher torque.

² One cycle covers forth and back the mechanical angle travel.

ENVIRONMENTAL TESTING


	Test method (CEI 393-1)	ΔR[%]- Piher typical test results
Electrical life	1.000h at 50°C; 0.15W	±5%
Mechanical life		
Potentiometer*	25.000 cycles at 10 to 15 cpm	±3% (R _n < 1MΩ)
Switch	10.000 cycles at 1A and 50 VAC	
Temperature coefficient	-25°C; +70°C	±300 ppm/°C (R _n < 100KΩ)
Thermal cycling	16h at 85°C and 2h at -25°C	±2.5%
Damp heat	500h at 40°C and 95% relative humidity (RH)	±5%
Vibration	2h each plane at 10Hz - 55Hz	±2%
Storage	6 month at 23°C ±2°C and 50% RH	±2.5%

* Only applicable to values > 1KΩ. For lower values please contact us.


Out of range values may not comply with these results. Standard test conditions: temperature: 23°C ±2°C and 45% to 70% RH

RECOMMENDED CONNECTIONS

Recommended connection circuit for a position sensor or control application (voltage divider circuit electronic design).




POWER RATING CURVE



PC-16

16-mm carbon panel mount potentiometer

HOW TO ORDER



1. Mounting style: Type "V" is only available in model "S" potentiometer and with printed circuit terminals.
2. Bushings: Type "10" has two parallel flat surfaces to avoid rotation. Bushless option only available for single model
3. --- = no shaft. The material for plastic shafts has "HB" rating UL94 classification.
4. Ω- Value: XXX - First two digits of Ω-value
XXX - Number of zeros
If you need tandem "D" models with several resistive values in each module, please contact Piher before ordering
5. Taper: switch option not available with Alog (reverse) taper. Log and Alog tapers available for Rn 1KΩ
6. Tolerance: ±5% tolerance available for values 1KΩ Rn 1MΩ. Custom tolerances available. Please contact Piher for more information
7. Custom shaft length (in mm): maximum recommended: 45mm.
8. Mounting brackets: only applicable for horizontal single models without switch
9. Stereo matching: not applicable to single models. Maximum spec.: 3dB
10. Not available for bushless type

 [check inventory](#)

ORDER CODE EXAMPLES

PC16SV-10IP16-105A2020-I-TA

Single body vertical adjust potentiometer with M10 bushing, PCB pin leads, "P16" shaft, 1MΩ resistive value, 20% resistive tolerance, switch with PCB pin leads and loose nut and washer.



PC16DH-07CP06-103A1010-15,0-MTA

Double body horizontal adjust potentiometer with M07 bushing, solder lug leads, "P06" shaft type, 10KΩ resistive value, 10% resistive tolerance, shaft cut to L=15mm and factory-assembled nut and washer.

CUSTOMIZATION POSSIBILITIES

Potentiometer + wires + connector

- ✓ Piher can deliver bespoke product design and adaptations to meet any form, fit and function, including leads, wire harness and interface connector.





16-mm carbon panel mount potentiometer

STANDARD CONFIGURATION

Shaft length	Standard length according to shaft's drawing
Mounting brackets	None
Stereo matching	Only on request
Switch	None
Nut and washer	None

MODELS

PC-16 S/D ...H...	PC-16 SV
 <p>Technical drawings of the PC-16 S/D ...H... sensor. The drawings include a side view, a top view, and a detail view of the mounting surface. The side view shows a cylindrical body with a threaded section. The top view shows a square body with four mounting holes. The detail view shows the mounting surface with a hole diameter of $\varnothing 1.3^{+0.1}$ and a 3x3 grid of holes. The legend identifies the contacts: S Wiper, E Final, and A Initial.</p>	 <p>Technical drawings of the PC-16 SV sensor. The drawings include a side view, a top view, and a detail view of the mounting surface. The side view shows a cylindrical body with a threaded section. The top view shows a square body with four mounting holes. The detail view shows the mounting surface with a hole diameter of $\varnothing 1.3^{+0.1}$ and a 3x3 grid of holes.</p>



Download STEP files here: www.piher.net

METALLIC SUPPORT (MOUNTING BRACKETS)


PC-16 SH.....M1	PC-16 SH.....M2

PC-16


16-mm carbon panel mount potentiometer

BUSHINGS


07



10




SC (BUSHLESS)




TERMINALS

C - Solder Lugs




I = PCB




NUTS & WASHERS


BUSHING 10



BUSHING 07



TAPERS




For more information on custom tapers contact Piher Sensing Systems.

PC-16


16-mm carbon panel mount potentiometer

OPEN CIRCUIT FEATURE





CCW on-off (A)

PCI
Cut track at the beginning
of the travel.



PCF
Cut track at the end
of the travel



CW on-off (E)

A = Initial S = Wiper E = Final.
PCI, PCF and other configurations available upon request. Check the ordering code with Piher.

PACKAGING

Bulk




Box dimensions (mm): 250x160x95


Units per box: 100 pcs

SWITCH

PC-16S ... H I / C



PC-16SV ... I



SWITCH SPECIFICATIONS

Nominal current	1A, 250 VAC
Contact resistance (initial)	10 mΩ
Operating torque	1 to 3 Ncm [1.4 to 4.2 in-oz]
Operating angle	30°±5°
Test voltage	500 V

360° CONTINUOUS ROTATION


STM-15




PC-16

16-mm carbon panel mount potentiometer

METALIC SHAFTS



Code	A	L
M04	4	45
M06	6	45



Code	A	B	C	L
M11	2	5	7	15
M12	2	10	11	20


Special models (check availability)



A
Ø 4
Ø 6


PLASTIC SHAFTS Ø3.1

P09




PLASTIC SHAFTS Ø4


P01




P02




P04




P07



P08



P10




PC-16

16-mm carbon panel mount potentiometer

PLASTIC SHAFTS Ø4

P21



PLASTIC SHAFTS Ø6

<p>P05</p>	<p>P06</p>	<p>P11</p>
<p>P12</p>	<p>P13</p>	<p>P14</p>
<p>P15</p>	<p>P16</p>	<p>P17</p>
<p>P18</p>	<p>P19</p>	<p>P20</p>
<p>P22</p>	<p>P23</p> <div data-bbox="1050 1921 1342 2078"> <p>18 teeth knurl with arrow shape shaft</p> </div>	

Shaft position shown full CCW. Any other position for plastic shafts has to be shifted n times 24°. Other positions upon request..

PC-16

16-mm carbon panel mount potentiometer

One Stop Shop

Multiple Advantages



Engineering
design-in
support



Output
customization



Cable harness and
connector assembly



One-stop solution provider for
different sensing
technologies



Global
footprint



Manufacturing
capabilities for high
and low volume
programs



Diverse portfolio of standard and customized
sensors: Tilt, Position, Speed and Current.

Hall-effect	TMR
Resistive	Inductive
Printed electronics	

OUR ADVANTAGE

- ▶ Leading-edge innovative position sensing solutions
 - ▷ Contactless (Hall-effect and Inductive Technology)
 - ▷ Contacting (Potentiometers, Printed Electronics)
- ▶ Engineering design-in support
- ▶ All our products can be customized to fit target application and customer requirement
- ▶ Capability to move seamlessly from development to true high-volume production
- ▶ A global footprint with global engineering and commercial support
- ▶ One-stop shop not limited to position sensors (temperature, pressure, gas,...) through group collaboration
- ▶ Flexibility and entrepreneurship of a medium-sized company with the backing of Amphenol Corporation



Please always use the latest updated datasheets and 3D models published on our website.

Disclaimer:

The product information in this catalog is for reference purposes. Please consult for the most up to date and accurate design information. Piher Sensors & Controls S.A., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Piher"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product described herein. Piher disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Piher's terms and conditions of sale, including but not limited to the warranty expressed therein, which apply to these products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Piher. The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Piher products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Piher for any damages arising or resulting from such use or sale. Please contact authorized Piher personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners. Information contained in and/or attached to this catalogue may be subject to export control regulations of the European Community, USA, or other countries. Each recipient of this document is responsible to ensure that usage and/or transfer of any information contained in this document complies with all relevant export control regulations. If you are in any doubt about the export control restrictions that apply to this information, please contact the sender immediately. For any Piher Exports, Note: All products / technologies are EAR99 Classified commodities. Exports from the United States are in accordance with the Export Administration Regulations. Diversion contrary to US law is prohibited.

CONTACT

Piher Sensing Systems
Polígono Industrial Municipal
Vial T2, N°22
31500 Tudela, Spain
sales@piher.net

+34 948 820 450



NEED QUICK HELP?

Our AI Virtual Assistant is available
24/7 to provide instant support—
visit chat.piher.info now!

Rev.180724 © 2024 Piher Sensors & Controls S.A.